

ENDURALINE

Built to last 100,000 hours

JOB NAME:

TYPE:

CATALOG #:

GENERAL DESCRIPTION:

A traditional garage luminaire, the IGL Series is a commercial luminaire, ideal for lower to medium mounting heights, and where minimum maintenance is critical.

HOUSING:

- Heavy duty die cast aluminum
- Stainless steel fasteners

OPTICS:

- Injection molded UV stabilized prismatic polycarbonate diffuser
- High reflectance white reflector

MOUNTING:

- ½ " side/rear threaded hubs
- J box mounting template on backplate.
- All units should be installed by a licensed electrical contractor in accordance with NEC guidelines.

ELECTRICAL / BALLAST:

Rated for 100,000 hrs, a 100% high frequency electronic ballast with .99pf, < 10% THD, Sound Rated A, and compliance with FCC EMI regulations. Operating temperatures of -35c to 90c and voltages of 120v or 277v. All wiring to be AWM, TFN, or THHN to comply with rated temperature requirements.

LAMP:

3200 lumens (40W), 6400 lumens (80W), 9600 lumens (120W), or 12800 lumens (160w) 80 lpw rated for 100000 hrs, a CRI of 85, flicker free instant starting with optional Kelvin temperatures of 2700-6500k in color.

FINISH:

- Architectural bronze finish standard.

LISTINGS / WARRANTY:

All products are UL listed and carry a 5 Year limited warranty. **Optional 10 year warranty available.**

NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

INDUCTION GARAGE LIGHT

IGL SERIES



DIAMETER 15" HEIGHT 11 ¼ "

ORDERING INFORMATION

Example: IGL-40-4-277

<u>SERIES</u>	<u>WATTS</u>	<u>COLOR</u>	<u>VOLTAGE</u>
IGL	40	2 (2700k)	120
	80	3 (3500k)	277
	120	4 (4100k)	
	160	5 (5000k)	
		6 (6500k)	

OPTIONS:

FUSING	FS
BLACK FINISH	BLK
WHITE FINISH	WHT