

# ENDURALINE

*Built to last 100,000 hours*

JOB NAME:

TYPE:

CATALOG #:

## GENERAL DESCRIPTION:

A small scale vandal resistant surface unit **IVR Series** is ideal for medium to high mounting heights.

## HOUSING:

- Heavy duty formed aluminum
- Stainless steel fasteners

## OPTICS:

- Injection molded prismatic polycarbonate lens
- Optional white polycarbonate lens
- White aluminum reflector

## MOUNTING:

- 1/2" Knock outs on the side and back
- J box mounting template on backplate.
- All units should be installed by a licensed electrical contractor in accordance with NEC guidelines.

## ELECTRICAL / BALLAST:

Rated for 100,000 hrs, a 100% high frequency electronic ballast with .99pf, < 10% THD, Sound Rated A, and compliance with FCC EMI regulations. Operating temperatures of -35c to 90c and voltages of 120v or 277v. All wiring to be AWM, TFN, or THHN to comply with rated temperature requirements.

## LAMP:

3200 lumens (40W), 6400 lumens (80W), or 9600 (120w) 80 lpw rated for 100000 hrs, a CRI of 85, flicker free instant starting with optional Kelvin temperatures of 2700-6500k in color.

## FINISH:

- Architectural bronze finish standard.

## LISTINGS / WARRANTY:

All products are UL listed and carry a 5 Year limited warranty. **Optional 10 year warranty available.**

**NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.**

## INDUCTION VANDAL LIGHT ROUND SERIES

### IVR SERIES



DIAMETER 15"  
DEPTH 7 7/8"

## ORDERING INFORMATION

**Example: IVR-CL-40-4-277**

<u>SERIES</u>	<u>OPTICS</u>	<u>WATTS</u>	<u>COLOR</u>	<u>VOLTAGE</u>
IVR	CL	40	2 (2700k)	120
	CLEAR	80	3 (3500k)	277
	PRISMATIC	120	4 (4100k)	
	POLYCARBONATE		5 (5000k) 6 (6500k)	

## OPTIONS:

WHITE POLYCARBONATE FUSING      **WP** (IN LIEU OF "CL")  
**FS**