

ENDURALINE

Built to last 100,000 hours

JOB NAME:

TYPE:

CATALOG #:

GENERAL DESCRIPTION:

A small scale vandal resistant surface unit **IVS Series** is ideal for medium to high mounting heights.

HOUSING:

- Heavy duty die cast aluminum
- Stainless steel fasteners

OPTICS:

- Injection molded prismatic polycarbonate lens
- Optional white polycarbonate lens
- White aluminum reflector

MOUNTING:

- 1/2" Knock outs on the side and back
- J box mounting template on backplate.
- All units should be installed by a licensed electrical contractor in accordance with NEC guidelines.

ELECTRICAL / BALLAST:

Rated for 100,000 hrs, a 100% high frequency electronic ballast with .99pf, < 10% THD, Sound Rated A, and compliance with FCC EMI regulations. Operating temperatures of -35c to 90c and voltages of 120v or 277v. All wiring to be AWM, TFN, or THHN to comply with rated temperature requirements.

LAMP:

3200 lumens (40W) or 6400 lumens (80W) 80 lpw rated for 100000 hrs, a CRI of 85, flicker free instant starting with optional Kelvin temperatures of 2700-6500k in color.

FINISH:

- Architectural bronze finish standard.

LISTINGS / WARRANTY:

All products are UL listed and carry a 5 Year limited warranty. **Optional 10 year warranty available.**

NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

INDUCTION VANDAL LIGHT SQUARE SERIES

IVS SERIES



WIDTH 12 3/8" HEIGHT 12 3/8"
DEPTH 8 5/8"

ORDERING INFORMATION

Example: IVS-CL-40-4-277

<u>SERIES</u>	<u>OPTICS</u>	<u>WATTS</u>	<u>COLOR</u>	<u>VOLTAGE</u>
IVS	CL	40	2 (2700k)	120
	CLEAR	80	3 (3500k)	277
	PRISMATIC		4 (4100k)	
	POLYCARBONATE		5 (5000k) 6 (6500k)	

OPTIONS:

WHITE POLYCARBONATE
FUSING

WP (IN LIEU OF "CL")
FS