

ENDURALINE

Built to last 100,000 hours

JOB NAME:

TYPE:

CATALOG #:

GENERAL DESCRIPTION:

A European styled architectural unit, the **RIBC Series** is a semi-recessed signature piece, ideal for lower to medium mounting heights, and where style is critical.

HOUSING:

- Heavy duty die cast aluminum
- Stainless steel fasteners
- Die cast aluminum collar

OPTICS:

- Tempered prismatic glass diffuser
- Optional sand blasted diffuser
- C=Cutoff face
- High reflectance white reflector

MOUNTING:

- Die cast aluminum recessing flange
- 1/2 " side/rear threaded hubs
- J box mounting template on backplate.
- All units should be installed by a licensed electrical contractor in accordance with NEC guidelines.

ELECTRICAL / BALLAST:

Rated for 100,000 hrs, a 100% high frequency electronic ballast with .99pf, < 10% THD, Sound Rated A, and compliance with FCC EMI regulations. Operating temperatures of -35c to 90c and voltages of 120v or 277v. All wiring to be AWM, TFN, or THHN to comply with rated temperature requirements.

LAMP:

3200 lumens (40W) OR 6400 lumens (80W), 80 lpw rated for 100000 hrs, a CRI of 85, flicker free instant starting with optional Kelvin temperatures of 2700-6500k in color.

FINISH:

- Architectural bronze finish standard.

LISTINGS / WARRANTY:

All products are UL listed and carry a 5 Year limited warranty. **Optional 10 year warranty available.**

NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

SEMI RECESSED OUTDOOR INDUCTION BULKHEAD CUTOFF RIBC SERIES



DIAMETER 15"
DEPTH 9 1/4"

ORDERING INFORMATION

Example: RIBC-PG-40-4-277

<u>SERIES</u>	<u>OPTICS</u>	<u>WATTS</u>	<u>COLOR</u>	<u>VOLTAGE</u>
RIBC	PG	40	2 (2700k)	120
CUTOFF	PRISMATIC GLASS	80	3 (3500k) 4 (4100k) 5 (5000k) 6 (6500k)	277

OPTIONS:

SAND BLAST DIFFUSER	SBD
FUSING	FS
BLACK FINISH	BLK
WHITE FINISH	WHT
PLATINUM	PLT
GREY	GRY