

ENDURALINE

∞ BUILT TO LAST ∞

JOB NAME:

TYPE:

CATALOG #:

GENERAL DESCRIPTION:

A medium scale vandal resistant surface unit **VLM Series** is ideal for low to medium mounting heights.

HOUSING:

- Heavy duty die cast aluminum
- Stainless steel fasteners

OPTICS:

- Injection molded prismatic polycarbonate lens
- Optional white polycarbonate lens
 - Suffix: "WP"
- White aluminum reflector

MOUNTING:

- Suitable for wall or ceiling
- J box mounting template on backplate.
- All units should be installed by a licensed electrical contractor in accordance with NEC guidelines.

ELECTRICAL / BALLAST:

- 4kv pulse rated medium base socket
- N (NPF Reactor) 120v
- HPF: M (Magnetic) E (Electronic)
- DT (HPF/DUAL TAP) 120/277v
- QT (HPF/QUADTAP)120-277v

LAMP:

- Horizontal medium base clear lamp
- PL/PLT LAMP
- **ALL LAMPS INCLUDED.**

FINISH:

- Architectural bronze finish standard.

LISTINGS / WARRANTY:

- UL listed Wet Location
- 1 Year limited warranty.

NOTE: Specifications' SUBJECT TO CHANGE WITHOUT NOTICE.

VANDAL LIGHT MEDIUM VLM SERIES



HID/PLT

WIDTH 9"
HEIGHT 9"
DEPTH 7 ¼ "



PL

WIDTH 8 ½ "
HEIGHT 8 ½ "
DEPTH 4 ¼ "

ORDERING INFORMATION

Example: VLM-35-HPS-120-N--LP

SERIES	WATTS	SOURCE	VOLTS	BALLAST	LAMP
VLM	213(2X13)	PL	120	M	LP
	142(1X42)	PLT	DT	E	LP
VLM	35	HPS	120	N	LP
	50				
	70				
	50	MH	DT	H	LP
	70		QT	H	LP